# DOW UNIVERSITY OF HEALTH SCIENCES, KARACHI



# TENDER DOGUMENT

TITLE OF THE JOB

MAINTENANCE & REPAIR OF DMC CAMPUS, DUHS, KARACHI

NIT # DUHS/P&D/2018/9475 DATED: JULY 20, 2018

OFFICE OF PROJECT DIRECTOR PLANNING & DEVELOPMENT DOW UNIVERSITY OF HEALTH SCIENCES, BABA-E-URDU ROAD, BESIDES CIVIL HOSPITAL, KARACHI TEL / FAX # 021-99216065

E-MAIL: rahim.khan@duhs.edu.pk

## SUBJECT: MAINTENANCE & REPAIR OF DMC CAMPUS, DUHS, KARACHI.

1. Having examined the tender documents including Instructions to Bidders, Bidding Data, and Conditions of Contract, Specifications, Drawings and Bill of Quantities for the execution of the

To,

#### THE PROJECT DIRECTOR

Planning & Development Department, Dow University of Health Sciences, Karachi.

above-named work, vany defects therein in Bill of Quantities for	n conform	ity with the	Condition	ns of Co	ntract, Specif		ū
(Rupees						) or	such other
sum as may be ascerta	ained in ac	cordance wit	h the said	conditio	ns.		
2. We/I understand th	at all the A	Appendices at	tached he	ereto form	n part of this l	oid.	
3. As security for due	e performa	nce of the ur	ndertaking	gs and ob	ligations of the	his bid, w	e/I submit
herewith a	bid	security	in	the	amount	of	Rupees
			(F	ls		)	drawn in
your favour or made period of	_days beg our bid is in the cont	cinning from accepted, to ract within the	the date, le commence time starting of 90	bid is ope the wor ated in Ap	ened.  rks and to coppendix-A to om the date fi	mplete the Bid. xed for op	e whole of pening the
same and it shall remote that period.			-	-	·		-
6. Unless and until a written acceptance the		-	•			together	with your
7. We do hereby dec arrangement with any				t any col	llusion, comp	arison of	figures or
8. We understand that	·		•			•	
9. We undertake, if o	our/my bid	is accepted,	to execut	te the Per	rformance Se	curity refe	erred to in

Clause 10 of Conditions of Contract for the due performance of the Contract.

In the capacity of Dated this	duly authoriz day of	zed to sign Bio	ds for and on be	ehalf of
Signature:				
(Name of Tenderer i (Seal) Address:	_			
				-
Witness:				
Signature: Name:				
Address:				

10. We confirm, if our bid is accepted, that all partners of the joint venture shall be liable jointly and severally for the execution of the Contract and the composition or the constitution of the

joint venture shall not be altered without the prior consent of the procuring agency.

# APPENDIX-A TO TENDER

1	Amount of Performing Security	2.5% of the Contract price. Total
	5	amount including performance
		security and retention money
		deducted from bills 5% of contract
		price stated in Letter of
		Acceptance.
2	Time for Furnishing Programme (Commencement	Withindays from the date
	of Work)	of receipt of Letter of Acceptance.
5	Time of Commencement	Within 10 days from the date of
		receipt of Project Director's Notice
		to Commence, This shall be issued
		after singing of Contract
		Agreement.
6	Time of Completion of Works	24 Months days from the date of
		Notice to Commence.
7	Amount of Liquidity Damages/ Delay Damages /	0.1% per day of Contract Price for
	Penalties	the work remains un-commenced
		and un-completed after due date up
		to maximum of 10% of Contract
		price and after that termination of
		contract after 07 day's notice.
8	Defect Liability Period/Period of Maintenance	90 days from the effective date of
		Taking over/ Completion
		Certificate.
9	Percentage of Retention Money	10% of the amount of the
		Interim/Running Payment
		Certificate.
10	Limit of Retention Money	5% of Contract Price stated in
		Letter of Acceptance.

Signature of Contractor /Seal of Firm Authorized representative of Firm

# **INSTRUCTIONS TO TENDERS**

- a) Project Director Planning & Development, Dow University of Health Sciences, calls tenders for the "MAINTENANCE & REPAIR OF DMC CAMPUS, DUHS, KARACHI" with the bill of quantities attached here to be submitted by or before 11:00 A.M on 16-08-2018. Tenders cost will not be reimbursed for any cost of any kind whatsoever incurred in connection with the preparations and submission of their tenders.
- b) The tender for the each work should be in the sealed envelope bearing name of the work / contractor / firm clearly marked and addressed to Project Director Planning & Development, Dow University of Health Sciences, Karachi.
- c) The tender may be delivered in person or sent by registered mail so as to reach on or before the date and time stated above. Any tender received after the stipulated time will not be considered regardless of the cause of delay.
- d) All tender are invited to the present for the opening of the tender in **16-08-2018** at 11:30 A.M. The name of each tenderer and his total contract price only will be read aloud and recorded.
- e) Any tender/tenders without earnest money will not be entertained. Earnest money of the awarding firm may be return after successful completion of work. If the supplier fails to commence or complete the awarded work within the stipulated time his/her work order will be cancelled as per rule and earnest money shall also be forfeited.
- f) Detailed particulars of the work / works can be seen in the Project Director Office on any working day during the office hours.
- g) Tender shall be made in the form supplied therefore, with all items and blanks properly filled in. all data and figures and the signature of persons signing the tender shall be in ink. The completed BOQ should be without interlineations, alterations or erasures but if these are necessary to correct errors made by the tenderer, person(s) signing the tender shall initial them. Conditional tenders will not accepted.
- h) All unit prices filled in the schedule of quantities shall be firm. The unit prices against each item of work and estimate amount and all other data called for shall be given.
- i) All prices quoted shall be deemed to include all costs of performing the works, including labour, material, income tax, duties, octori charges, royalties permit etc. and no claim whatsoever shall be accepted in case of escalation any or all prices entered in rate of bid.
- j) The actual sum to be paid to the contractor whose tender is accepted shall be determined by measuring the work actually done or supplying/repairing the actual number of items in accordance with the work order and valuing it al the rate or prices by the contractor in the tender.
- k) "In-case of discrepancy between the unit price and amount entered for any item in the schedule of quantities, the unit price will be taken as correct and the amount will be adjusted accordingly when the tender is being examined".
- 1) 10 % security deposit will be deducted from each bill on the paid amount of the contract, which will be returned after maintenance period of 03 months.

- m) The tender must be signed in each and every page by a person(s) authorized to do so.
- n) The site can be visited on any working day during the office hours.
- o) "Engineer" means the Project Director Planning & Development of the University or any other Engineer appointed by him.
- p) The earnest money will be forfeited in case the contractor fails to commence the work within 10 days time after issue of work order or left the work incomplete after commencement and during execution.
- q) The Competent Authority reserve the right to reject any or all the tenders, increase or decrease the scope of work or divide item of work among bidders.
- r) That the Contractor shall be responsible to keep in good condition the premises of the University and shall not damage any property belonging to student of the University and incase of any loss damage caused by the contractors or its employee to any property of the compensate and or indemnify the university or the student as the case may be.

#### PROJECT DIRECTOR

Planning & Development Department Dow University of Health Sciences, Karachi

# DOW UNIVERSITY OF HEALTH SCIENCES, KARACHI

#### DIRECTORATE OF PLANNING & DEVELOPMENT

#### **TERMS & CONDITIONS**

- 1. The work / supply is required within 10 Days from the date of letter of Commencement/award.
- 2. Inspection: Nominated Inspection Committee will make Inspection of Work.
- 3. In case of late delivery @ 0.1% per day will be charged on bid amount deducted from the bill, but not more than 10% of contract value.
- 4. Quantities shown in the quotation are approximate and no claim shall be entertained for quantities of executed being 30% more or less than those entered in the BOQ.
- 5. All prices will include all costs of performing the works including labour, material, Income Tax, GST, Octroi Charges, royalties & transportation etc., as mentioned in BOQ.
- 6. No subletting of all or any part of work will be allowed at any cost / reasons.
- 7. The supplier will see the site / sample before quoting the rates.
- 8. Store will be delivered at Dow University of Health Sciences, Karachi.
- 9. Central Stores and Inspection Officer will issue inspection certificate after inspection through Inspection Committee.
- 10. If the work / supply is not found according to the specification and samples provided, will be rejected at risk and cost of the manufacturer and in case the manufacturer fails to work / supply the order, the firm will be black listed.

#### 11. Payment:

- The Actual sum to be paid shall be determined by quantifying / measurements of items actually supplied valuing it at the rates/prices quoted in the approved quotations.
- 11.2 10% security deposit will be retained from each bill upto a period of six months from the date of supply of order.
- Part payment against part supply can be allowed.
- 12. Request letter for issuance of tender documents should be supported with:
  - a. Copy of GST, SST & NTN registration Certificate and PEC Registration in appropriate category with the following codes BC01 BC02 CE01 CE04 CE09 CE10 EE01 EE02 EE04 EE06 EE07 EE08 EE11 ME01 ME02 ME03 ME06. (MANDATORY)
  - b. Copies of all relevant Certificate/Authorization letter must be attached (where required) mentioned with Tender Enquiry.
- 13. The bidder must have done at least five (05) contracts of similar nature and magnitude "Similar nature means Construction of Building preferable at educational institutes and hospitals" (Please submit copy of PO/Contract Agreement/Notification of Award). Comply with specifications mentioned in bidding documents.
- 14. The Bidder should not have been barred of any of provincial or federal Govt. Deptt Agency, organization or autonomous body or private sector organization anywhere in Pakistan. (Submission of undertaking on 100/- legal stamp paper). All the proposed reports should be well known for its quality, performance and reliability.

- 15. The bidder must have turnover/sales exceeding **400 Million** in PKR annually in any of last three years (Submission of Audited Annual Reports or reputable Bank confirmation letter.
- 16. Latest income Tax Certificate (NTN), valid GST Registration Certificate and valid SRB registration.

## PROJECT DIRECTOR

Planning & Development Department Dow University of Health Sciences, Karachi

# MAINTENANCE & REPAIR OF DMC AND IPM&R CAMPUS, DUHS, KARACHI

# ABSTRACT

S. No.	Item of Work	Amount
1	CIVIL WORK	
2	INTERNAL WATER SUPPLY & SANITARY FITTINGS	
3	INTERNAL WATER SUI GAS FITTINGS	
4	INTERNAL ELECTRIFICATION	
5	HVAC WORK	
6	DATA AND VOICE	
	TOTAL AMOUNT RS.	

CONTRACTOR	

Sr#	Description Of Items	Quantity	Rate	Unit	Amount
	PART 'A' CIVIL	WORK :-			
1	Dismantling of Existing Block / Stone Masonry and disposal of rubbish materials by mean of Tractor Trolly or Dumper.	3,000		P.Cft	
2	Dismantling of Existing flooring / skirting i/c C.C layer and disposal of rubbish materials by mean of Tractor Trolly.	38,075		P.Cft	
3	Dismantling of C.C.Plain and disposal of rubbish materials by mean of Tractor Trolly or Dumper. a) 1:2:4 b) 1:4:8	1,450 2,000		P.Cft P.Cft	
4	Dismantling cement concrete reinforced separating reinforcement and disposal of rubbish materials by mean of Tractor Trolly or Dumper.	2,000		P.Cft	
5	Removing cement or lime plaster from walls i/c removal rubbish materials from site of work by means of tractor trolly or dumper.	13,000		P.Sft	
6	Turfing slops of banks or lawns with grass sods including ploughing laying, setting and watering turf got from within a distance of 5 miles and maintenance for 15 days. This rate also i/c cost of filling 3" Thick layer of BHALLU SAND where as required and the cost of manure etc complete in all respects.	6,500		P.Sft	
7	Providing and Fixing upto 1-1/2" inches of thick approved Envicrete tiles / block (Size 16" x 8") Colored in wall at ground floor, over ½" or ¾" inch thick base of cement mortar 1:3 setting of tiles in slurry of grey cement over mortar base including filling the joints and washing the tiles white cement slurry curing and cleaning etc. complete (Envicrete / Megna crete tiles)	4,000		P.Sft	
8	Excavation in foundation of buildings, bridges and other structures as per required section, including dag belling, dressing filling around structure with excavated earth watering ramming& compacting etc complete in all respects as per specifications provided and instruction given by the Engineer Incharge. Lead up to 300 Feet & lift up to 6 feet.  (i) IN ALL TYPE OF SOILS EXCEPT HARD				
	ROCK	950		P.Cft	

9	Cement Concrete Plain including placing compacting, finishing and curing complete (including screening and washing of crush bajri) without form work . etc complete in all respects as per specifications provided and instructions given by the Engineer Incharge. Ratio 1:4:8 (CLASS 'E') (Under Foundation Using S.R Cement)	6,000	P.Cft	
10	Cement Concrete Plain including placing compacting, finishing and curing complete (including screening and washing of crush bajri) without form work . etc complete in all respects as per specifications provided and instructions given by the Engineer Incharge. Ratio 1:2:4 (CLASS 'C') (Under Floor Using O.P.C Cement) (Under Floor Using S.R Cement)	4,500 2,750	P.Cft P.Cft	
11	Cleaning Surface, Rubbing and Re-grinding & Chemical Polishing of Existing Marble Flooring etc complete in all respects.	4,560	P.Sft	
12	Coursed rubble masonry including hammer dressing. In Cement Sand Mortar (i) 1 Cement : 3 Sand.	500	P. Cft	
13	Providing fabricating and fixing light gauge structural steel in walls. Partition Walls, Roof Truss, Roof frames, bracings, columns etc. all framing element with C-Section having profile 89mm x41mm x 0.75mm thick (Manufactured by Framecad or Equivalent) GI Prime Quality Steel G550 with coating of Z-275 g/m2 conforming to ASTM A653 or equivalent hot dipped galvanized including imported approved quality screws for the connection of elements and all other part required for the fixing complete in all respect as per design / drawings and specification and as per instructions of the Project Manager / Project Engineer / Consultant. Measurement of covered area.	2,000	P.Sft	
15	Providing and laying Class 'D' 1:3:6 cement concrete solid block masonry set in 1:6 cement sand i/c minor reinforcement at concrete joints, racking of joints and curing, etc, complete. In Plinth & Floor Area	0.000	D.C.	
	(Minimum crushing strength 1300-lbs/PSI)	2,000	P.Cft	

16	Providing and laying Class 'D' 1:3:6 cement concrete Solid Block Masonry wall 4" to 8" in thickness and above set in 1:6 cement sand mortar in ground floor superstructure i/c racking of joints and curing, etc, complete.(Minimum crushing strength 1300-lbs/P.S.I)  150 mm Thick 200 mm Thick 100 mm Thick	4,000 6,000 2,000	P.Sft P.Sft P.Sft	
17	Providing and laying plain cement concrete Class "D" (1:3:6) in foundation having minimum works cube crushing strength of 1500 lbs. per sq. inch at 28 days for blinding or under floors where required using approved quality 1" maximum size graded crushed stone or gravel with approved quality sand including all formwork, roding, leveling, compacting and curing etc. complete as per specifications, drawings and to the entire satisfaction of Engineer. Ratio 1:3:6 (CLASS 'D') (Under Foundation Using S.R Cement)	1,500	P.Cft	
18	Providing & fixing cement paving blocks flooring having size of 200 x 100 x 60 (mm) of City / Quadra / Cobble shape in a specified pattern and design with the combination of natural colour and colored blocks, having strength b/w 4000 lbs./Sft to 6000 lbs./Sft over 2" thick compact bed of crush ash i/c filling the joints with river sand and also i/c proper compaction with compactor machine after laying blocks etc complete in all respect as per specification provided and instructions given by the Engineer Incharge.	4,400	Sft	
19	BITU-POLE Treatment to plastered or exposed Concrete Surface under foundation to be buried in trench as directed by Engineer Incharge	2,200	Sft	
20	Cement Plaster in Ratio 1:6 (15 mm Thick) i/c floating coat of cement in proper design & profile on walls/beams & columns .This rate also i/c providing expanded metal at the joint of R.C.C.members and block masonry where as required etc complete in all respects as per specifications and drawings and approval of Engineer Incharge (i) 15 mm thick Internal / External	18,000	P.Sft	

21	Cement Plaster in Ratio 1:4 (13 mm Thick) i/c floating coat of cement in proper design and profile on walls, beams & columns etc complete in all respects as per specifications and drawings and approval of Engineer Incharge.  (i) 13 mm thick Internal / External	17,000	P.Sft	
22	M / Fixing Teak Wood Chowkat size i/c hold fasts and fixing in block or brick masonry etc complete in all respects as per directives of Engineer Incharge. a) 7-1/2" x 2" b) 9-1/2" x 2" c)13-1/2"x 2"	300 200 175	P.Rft P.Rft P.Rft	
23	Fabrication of Deformed Steel Bars, reinforcement for cement concrete work i/c cutting, bending, laying in proper position, making joints & fastenings etc complete. This rate include cost of binding wire, over lapping, extra wastage, laboratory testing of steel and removing rust from bars. (Grade 60, Minimum Yield Strength 60000 Lbs / P.S.I.	7	PTon	
24	Providing and laying R.C.C Class 'C'(1:2:4 having a minimum crushing strength of 3000 PS I at 28 days), using 6mm to 18mm sizes graded crushed aggregate and fine aggregate including approved quality form work and its removal, all operations of vibrating, leveling, consolidating, curing and cube / cylinder lab tests of pouring material at 07 days & 28 days etc. Complete in all respects as per specifications and drawings and approval of Engineer Incharge .This rate does not includes the cost of steel bars and its erection which will be paid separately (General Mould)	700	P.Cft	
25	Providing and laying R.C.C Class 'B'(Ratio 1:1-1/2:3 having a minimum crushing strength of 4000 PSI at 28 days), using 6mm to 18mm sizes graded crushed aggregate and fine aggregate including approved quality form work and its removal, all operations of vibrating, leveling, consolidating, curing and cube / cylinder lab tests of pouring material at 07 days & 28 days etc. Complete in all respects as per specifications and drawings and approval of Engineer Incharge .This rate does not includes the cost of steel bars and its errection which will be paid separately (General Mould)	<b>F</b> 00	D 01	
	(Contract modia)	500	P.Cft	

18 yauge for doors i/c pouring C.C. 1:2:4 inside chowkat etc: complete in all respect. a) 2'* 99/* b) 2" x 7½* c) 2' x 13½* c) 2' x 13½* Trowiding and laying Topping of cement concrete (1:2:4) including surface finishing & dividing into panels. a) 3" thick b) 2" thick  27 Providing and fixing in position Doors Shutter 1-1/2' thick Teak wood ply shutters (Partially glazed with frost glass where as required) over first class partal wood skelton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, into tower boths, handles and cleats with cord etc complete in all respects. a) 1-1/2' thick  29 Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  30 Providing and fixing Door Closer of approved & Design (Imported).  31 Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long d) 18" Long a) 12" long 1/2" dia b) 12" long 1/2" dia b) 12" long 5/8" dia  34 Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  35 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long b) 6" long c) 70 Fach c) Fa	26	Providing and fixing G.I. sheet chowkats of			
inside chowkat etc: complete in all respect. a) 2" x 9½" b) 2" x 7½" c) 2' x 13½"  27 Providing and laying Topping of cement concrete (1:2-¼) including surface finishing & dividing into panels. a) 3" thick b) 2" thick b) 2" thick c) 3,750  28 Providing and fixing in position Doors Shutter 1-1/2" thick Teak wood ply shutters (Partially glazed with frost glass where as required) over first class partal wood skeleton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower bolts, handles and cleats with cord etc complete in all respects. a) 1-1/2" thick c) Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported). d) Each c) Providing and fixing Door Closer of approved & Design (Imported). d) Each c) Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long. c) 12" Long. d) 18" Long. d) 1	20				
a) 2" x 9½" b) 2" x 7½" c) 2' x 13½"  27 Providing and laying Topping of cement concrete (1:2:4) including surface finishing & dividing into panels. a) 3" thick b) 2" thick  28 Providing and fixing in position Doors Shutter 1-1/2" thick Teak wood ply shutters (Partially glazed with frost glass where as required) over first class partal wood skelton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower boths, handles and cleats with cord etc complete in all respects. a) 1-1/2" thick  29 Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  30 Providing and fixing Door Closer of approved & Design (Imported).  31 Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long c) 12" Long d) 18" Long e) 12" long 5/8" dia  20 Each  31 Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  32 Providing and fixing C.P Brass Handle. a) 5" long b) 6" long b) 6" long b) 6" long c) 10 Each  34 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick					
b) 2" x 7½" c) 2 x 13½" c) 2 x 13½ c) 2 x 15½		·	150	P Rft	
c) 2' x 13½"  Providing and laying Topping of cement concrete (1:2-4) including surface finishing & dividing into panels.  a) 3" thick b) 2" thick  13,000 P.Sft 3,750  P.Sft  28 Providing and fixing in position Doors Shutter 1-1/2" thick Teak wood ply shutters (Partially glazed with frost glass where as required) over first class partal wood skeleton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower bolts, handles and cleats with cord etc complete in all respects. a) 1-1/2" thick  450 P.Sft  Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  Providing and fixing Door Closer of approved & Design (Imported).  Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long D) 8" Long D) 12" long 5/8" dia  Providing and fixing Aldrop. a) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  Fach  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  Fach  Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" with specified colour having water, fire3 and termite resistance o		,			
Providing and laying Topping of cement concrete (1:2:4) including surface finishing & dividing into panels. a) 3" thick b) 2" thick 13,000 P.Sft 3,750 P.Sft  28 Providing and fixing in position Doors Shutter 1-1/2" thick Teak wood ply shutters (Partially glazed with frost glass where as required) over first class partal wood skeleton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower bolts, handles and cleats with cord etc complete in all respects. a) 1-1/2" thick  29 Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  80 Each  Providing and fixing Door Closer of approved & Design (Imported).  130 Each  Providing and fixing Brass Tower Bolts. a) 6" Long, b) 8" Long c) 12" Long d) 18" Long c) 12" Long d) 18" Long c) 12" long 1/2" dia b) 12" long 1/2" dia b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  70 Each  21 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  22 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  35 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" withs specified colour having water, fire3 and termite resistance over the base of 1/2" withs		,			
concrete (1:2:4) including surface finishing & dividing into panels.  a) 3" thick b) 2" thick 3,750 P.Sft b) 2" thick Teak wood ply shutters (Partially glazed with frost glass where as required) over first class partal wood skeleton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower bolts, handles and cleats with cord etc complete in all respects. a) 1-1/2" thick 450 P.Sft Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  80 Each Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported). 40 Each Providing and fixing Door Closer of approved & Design (Imported). 41 Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long 70 Each Each 32 Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia 20 Each 33 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long 34 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long 35 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick		3, =	100	1	
concrete (1:2:4) including surface finishing & dividing into panels.  a) 3" thick b) 2" thick  28 Providing and fixing in position Doors Shutter 1-1/2" thick Teak wood ply shutters (Partially glazed with frost glass where as required) over first class partal wood skeleton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower bolts, handles and cleats with cord etc complete in all respects. a) 1-1/2" thick  29 Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  80 Each  70 Providing and fixing Door Closer of approved & Design (Imported).  81 Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long 70 Each  82 Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  83 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long 34 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long 55 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick	27	Providing and laying Topping of cement			
a) 3" thick b) 2" thick 28 Providing and fixing in position Doors Shutter 1-1/2" thick Teak wood ply shutters (Partially glazed with frost glass where as required) over first class partal wood skeleton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower bolts, handles and cleats with cord etc complete in all respects. a) 1-1/2" thick 450 P.Sft  Poviding and fixing C.P Brass Mortice Lock with Round Handle (Imported).  Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  Providing and fixing Door Closer of approved & Design (Imported).  Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long Too Each  Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  Fach  P.Sft P.Sf		concrete (1:2:4) including surface finishing &			
b) 2" thick  B) 2" thick  Broviding and fixing in position Doors Shutter 1-1/2" thick Teak wood ply shutters (Partially glazed with frost glass where as required) over first class partal wood skeleton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower boths, handles and cleats with cord etc complete in all respects.  a) 1-1/2" thick  Broviding and fixing C.P Brass Mortice Lock with Round Handle (Imported).  Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  Providing and fixing Door Closer of approved & Design (Imported).  Providing and fixing Brass Tower Bolts.  a) 6" Long.  b) 8" Long  c) 12" Long  d) 18" Long  Providing and fixing Aldrop.  a) 12" long 1/2" dia  b) 12" long 1/2" dia  b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle.  a) 5" long  b) 6" long  30 Each  Bach  B		dividing into panels.			
Providing and fixing in position Doors Shutter 1-1/2" thick Teak wood ply shutters (Partially glazed with frost glass where as required) over first class partal wood skeleton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower bolts, handles and cleats with cord etc complete in all respects. a) 1-1/2" thick  450  Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  Providing and fixing Door Closer of approved & Design (Imported).  Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long d) 18" Long d) 18" Long Troviding and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long 30  Each  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  Froviding & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick		a) 3" thick	13,000	P.Sft	
1-1/2" thick Teak wood ply shutters (Partially glazed with frost glass where as required) over first class partal wood skeleton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower botts, handles and cleats with cord etc complete in all respects. a) 1-1/2" thick  29 Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  30 Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  31 Providing and fixing Door Closer of approved & Design (Imported).  32 Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long 70 Each  33 Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  20 Each 21 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  30 Each  31 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick		b) 2" thick	3,750	P.Sft	
1-1/2" thick Teak wood ply shutters (Partially glazed with frost glass where as required) over first class partal wood skeleton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower botts, handles and cleats with cord etc complete in all respects. a) 1-1/2" thick  29 Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  30 Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  31 Providing and fixing Door Closer of approved & Design (Imported).  32 Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long 70 Each  33 Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  20 Each 21 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  30 Each  31 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick					
glazed with frost glass where as required over first class partal wood skeleton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower bolts, handles and cleats with cord etc complete in all respects.  a) 1-1/2" thick  450  Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  80  Froviding and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  130  Providing and fixing Door Closer of approved & Design (Imported).  130  Fach  29  Providing and fixing Brass Tower Bolts.  a) 6" Long. b) 8" Long c) 12" Long d) 18" Long 70 Each 70	28				
over first class partal wood skeleton (Solid) styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower bolts, handles and cleats with cord etc complete in all respects. a) 1-1/2" thick  29 Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  30 Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  31 Providing and fixing Door Closer of approved & Design (Imported).  32 Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long 70 Each 31 Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  20 Each 21 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  30 Each 21 Each 22 Each 23 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  30 Each 31 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick					
styles and rails core of partal wood and Teak ply wood (3 ply) on both sides including hold fasts, hinges, iron tower bolts, handles and cleats with cord etc complete in all respects.  a) 1-1/2" thick  29 Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  30 Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  31 Providing and fixing Door Closer of approved & Design (Imported).  32 Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long d) 18" Long 33 Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  34 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  35 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick					
ply wood (3 ply) on both sides including hold fasts, hinges, iron tower bolts, handles and cleats with cord etc complete in all respects. a) 1-1/2" thick  29 Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  30 Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  31 Providing and fixing Door Closer of approved & Design (Imported).  32 Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long d) 18" Long 30 Each 31 Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  32 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long 33 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  34 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick		• • • • • • • • • • • • • • • • • • • •			
cleats with cord etc complete in all respects. a) 1-1/2" thick  29 Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  80 Each  Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  40 Each  Providing and fixing Door Closer of approved & Design (Imported).  Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long c) 12" Long d) 18" Long  Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  30 Each  31 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick					
a) 1-1/2" thick  29 Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  30 Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  31 Providing and fixing Door Closer of approved & Design (Imported).  32 Providing and fixing Brass Tower Bolts. a) 6" Long. b) 8" Long. c) 12" Long d) 18" Long  33 Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  34 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long 35 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick		1			
Providing and fixing C.P Brass Mortice Lock with Round Handle (Imported).  Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  Providing and fixing Door Closer of approved & Design (Imported).  Providing and fixing Brass Tower Bolts.  a) 6" Long.  b) 8" Long  c) 12" Long  d) 18" Long  70  Each  Providing and fixing Aldrop.  a) 12" long 1/2" dia b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2 " thick		•			
with Round Handle (Imported).  80 Each  Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  Providing and fixing Door Closer of approved & Design (Imported).  Providing and fixing Brass Tower Bolts.  a) 6" Long. b) 8" Long. c) 12" Long d) 18" Long 70 Each  Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick		a) 1-1/2" thick	450	P.Sft	
with Round Handle (Imported).  80 Each  Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  Providing and fixing Door Closer of approved & Design (Imported).  Providing and fixing Brass Tower Bolts.  a) 6" Long. b) 8" Long. c) 12" Long d) 18" Long 70 Each  Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick	20	Brouiding and fiving C.B. Bross Martins Look			
Providing and fixing C.P Brass Mortice Lock with Long Handle (Heavy Design Imported).  Providing and fixing Door Closer of approved & Design (Imported).  Providing and fixing Brass Tower Bolts.  a) 6" Long. b) 8" Long c) 12" Long d) 18" Long 70 Each  Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick	29		00	Fook	
with Long Handle (Heavy Design Imported).  Providing and fixing Door Closer of approved & Design (Imported).  Providing and fixing Brass Tower Bolts.  a) 6" Long. b) 8" Long c) 12" Long d) 18" Long 70 Each  Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick		Will reduid Flandio (imperiod).	00	Each	
with Long Handle (Heavy Design Imported).  Providing and fixing Door Closer of approved & Design (Imported).  Providing and fixing Brass Tower Bolts.  a) 6" Long. b) 8" Long c) 12" Long d) 18" Long 70 Each  32 Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  35 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick	30	Providing and fixing C.P. Brass Mortice Lock			
Providing and fixing Door Closer of approved & Design (Imported).  130  Providing and fixing Brass Tower Bolts.  a) 6" Long. b) 8" Long c) 12" Long d) 18" Long 70 Each  130  Each  85 Each Each Each Each Each Each Each Each			40	Fach	
& Design (Imported).  130  Each  Providing and fixing Brass Tower Bolts.  a) 6" Long. b) 8" Long c) 12" Long d) 18" Long 70 Each d) 18" Long 70 Each Each 70 Each Each 20 Each b) 12" long 1/2" dia b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick			10	Laon	
& Design (Imported).  130  Each  Providing and fixing Brass Tower Bolts.  a) 6" Long. b) 8" Long c) 12" Long d) 18" Long 70 Each  Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2" thick	31	Providing and fixing Door Closer of approved			
a) 6" Long. b) 8" Long c) 12" Long d) 18" Long  70 Each 80 Each 70 Each 70 Each 80 Each 70 Each 70 Each 80 Each 70 Each 80 Eac		& Design (Imported).	130	Each	
a) 6" Long. b) 8" Long c) 12" Long d) 18" Long  70 Each 80 Each 70 Each 70 Each 80 Each 70 Each 70 Each 80 Each 70 Each 80 Eac					
b) 8" Long c) 12" Long d) 18" Long  33 Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  20 Each 20 Each 34 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  36 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2 " thick	32	Providing and fixing Brass Tower Bolts.			
c) 12" Long d) 18" Long  70 Each T70  8		, ,	85	Each	
d) 18" Long  70  Each  70  Providing and fixing Aldrop. a) 12" long 1/2" dia b) 12" long 5/8" dia  20  Each  20  Each  20  Each  Each  34  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  30  Each  31  Each  Eac		, ,	80	Each	
Providing and fixing Aldrop.  a) 12" long 1/2" dia b) 12" long 5/8" dia  20 Each Each  20 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2 " thick		, ,			
a) 12" long 1/2" dia b) 12" long 5/8" dia  20 Each 20  34 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  30 Each Each 31  Each Each 32  Each Each 33  Each Each 30  Each Each Each 30  Each Each Each 20  Each Each Each Each 20  Each Each Each Each Each Each Each Eac		d) 18" Long	70	Each	
a) 12" long 1/2" dia b) 12" long 5/8" dia  20 Each 20  34 Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  30 Each Each 31  Each Each 32  Each Each 33  Each Each 30  Each Each Each 30  Each Each Each 20  Each Each Each Each 20  Each Each Each Each Each Each Each Eac	20	Droviding and fiving Aldran			
b) 12" long 5/8" dia  20  Each  Providing & fixing C.P Brass Handle. a) 5" long b) 6" long  30 Each  Each  Each  Sach  Each  Each  Each  Sach  Each  Sach  Each  Sach  Each  Each  Each  Sach  Each  Each  Each  Each  Sach  Each  Each  Each  Each  Each  Each  Each  Sach  Each  E	33		00	F	
Providing & fixing C.P Brass Handle.  a) 5" long  b) 6" long  30  Each Each  Surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2 " thick		, , <u> </u>			
a) 5" long  30 Bach b) 6" long  30 Bach Each  35 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2 " thick		0/ 12   1011g 3/0   ula	20	⊏acn	
a) 5" long  30 Bach b) 6" long  30 Bach Each  35 Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2 " thick	34	Providing & fixing C.P Brass Handle			
b) 6" long  30  Each  Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2 " thick	"		30	Fach	
Providing & fixing Colour Crete to wall surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2 " thick		, · · · · · · · · · · · · · · · · · · ·			
surface to provide, durable crust and aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2 " thick					
aesthetics having thickness upto 1/2" with specified colour having water, fire3 and termite resistance over the base of 1/2 " thick	35				
specified colour having water, fire3 and termite resistance over the base of 1/2 " thick					
termite resistance over the base of 1/2 " thick					
			4.398	P.Sft	
			,		

36	Providing & Applying water proofing Membrane Korean PE canvas sheet on earth Filling in bed as per specification & instruction of Engineer.	1,500	P.Sft	
37	Providing and Applying French polishing over wood work with liqueur base spirit polish and filling material etc complete in all respect.	4,500	P.Sft	
38	Providing and laying precast roof with girder 4"x9".of approved make & design.	2,500	P.Sft	
39	Preparing surface and Applying water proofing chemical 1st primary coat of 26 AC 10/55 chemical and then heavy rich coat with canvas cloth and in last two coats of same chemical etc complete in all respects as per directives of Engineer Incharge.	14,666	P.Sft	
40	Providing and spraying pesticide solution of approved manufacturer inside building line in 3 - stages i.e. in trenches, on floor base & all wood work etc, using "Agenda" or equivalent of Jaffer Brothers water mixed solution.	10,000	P.Sft	
41	Providing & fixing mild steel louver door & window with angle framing chowkat 1-1/2" x 1-1/2" 6mm thick door framing 1/1/4" x 1/1/4" thick angle with mild steel sheet 16 swg for louver with all respect accessories, painting 3 coats.	1,200	P.Sft	
42	Providing & fixing iron bar grill gate with angle frame angle Iron 1"x1" & solid square bar 3/8" x 3/8" with 6" c/c all respect accessories with locking arrangement, painting 3 coats of enamel paint etc complete in all respects.	850	P.Sft	
43	Providing and Fixing picture railing with screwing and nails. Etc complete in all respects including French polishing.			
	a) 2" thick Oak wood b) 2 1/2" thick Oak wood c) 2" thick Golden Teak	500 400 1,300	P.Rft P.Rft P.Rft	
44	Providing & Fixing Imported Fixed Glass 8 m clear with necessary frame channel of Aluminum.	1,500	P.Sft	
45	Providing & Fixing Imported Fixed Glass 12 mm clear with necessary frame channel of Aluminum	950	P.Sft	

46	Providing and fixing 12 mm thick glass partition with door i/c floor hinge imported machine, pasting frost paper and S.S. 18" long handle ETC complete in all respect.	650	P.Sft
47	Providing & Fixing Banko imported Hinge Machine.	90	Each
48	Providing & Fixing Stainless Steel push plate (JB Saeed)	50	Each
49	Removing old Aluminum Door with motor and aluminum partition etc complete	650	P.Sft
50	S/F in position Aluminum box channels framing (100 mm x 40 mm) for office chamber partitions i/c Aluminum hinged doors made (of approved make and design) with Aluminum Sheet 3 mm on bottom up to 300 mm height, 5 mm thick tinted frost glass glazed on remaining portion, imported Door Closer over Door and Alpha (Japan) locks including handles stoppers etc complete in all respects as per directives of Engineer Incharge. (Prime / Chawla or Equivalent)	1,200	P.Sft
51	S/F in position Aluminum box channels framing (100 mm x 40 mm) for Aluminum Doors made (of approved make and design) with Aluminum Sheet 3 mm on bottom up to 900 mm height, 5 mm thick tinted frost glass glazed on remaining portion (Belgium), imported floor hinge two way pivot machine and Alpha (Japan) locks including handles stoppers etc complete in all respects as per directives of Engineer In charge. (Prime/ Chawela or Equivalent)	400	P.Sft
52	S/F in position Aluminums channels framing (100mm x 40 mm) for sliding windows & ventilator with collar made (of approved make and design) with 5 mm thick tinted glass glazing (Belgium) and aluminum fly screen channel including handles stoppers & locking arrangements etc complete in all respects as per directives of Engineer In charge (Prime/ Chawla or Equivalent)		
	· · · · · · · · · · · · · · · · · · ·	800	P.Sft

53	Supplying and fixing Steel grill of 1/2" x 1/2" square bar as per approved design (Weight 2.00 kg / Sq. ft.:) i/c Painting2 coats of oil paint with one coat red oxide paint etc: complete in all respects as per specifications and drawings and approval of Engineer In charge.	750	P.Sft	
54	Applying 3 Coats of Plastic Bound Distemper Paint i/c primary coat of chalk and preparing base surface and filling where as required as per requirement of Architecture Drawings and specifications etc complete in all respects as per directives of Engineer In charge.	30,000	P.Sft	
55	Applying 3 Coats of Silk Matt Finishing with primary coat and preparing base surface and filling where as required as per requirement of Architecture Drawings and specifications etc complete in all respects as per directives of Engineer In charge.	55,000	P.Sft	
56	P/Applying 3 Coats of Weather Shield Paint of superior quality i/c preparing base surface and filling etc complete in all respects as per directives of Engineer In charge	22,000	P.Sft	
57	Preparing surface and oil painting Doors and Windows any type including edges (Iron or wooden or partially glazed)	6,300	P.Sft	
58	Providing and fixing Printed Granite / Porcelain Tiles Flooring jointed in white cement and laid over bed of 1"to 2" thick grey cement concrete bed in ratio 1:2:4 i/c washing / filling of joints with white cement etc: complete in all respect (Imported Premium Quality costing Rs 1800 per meter or above) as per sample approved by Engineer etc complete.			
a	Flooring	13,500	P.Sft	
b c	Wall Dado 6" Wide Wall Border	3,000 2,000	P.Sft P.Rft	
59	Providing and fixing Printed Glazed Ceramic Tiles Flooring jointed in white cement and laid over bed of 1/2"thick grey cement send mortar ratio 1:3 i/c washing / filling of joints with white cement etc: complete in all respect (Imported Premium Quality costing Rs 1600 per square meter or above) as per sample approved by Engineer etc complete.	0.500	D 0"	
	Wash Rooms Flooring	2,500	P.Sft	

60	Providing and fixing Printed Glazed Ceramic Tile Dado/ Skirting i/c two layers of Printed Borders (2" to 4"Wide) jointed in white cement and laid over bed of 1/2"thick grey cement send mortar ratio 1:3 i/c washing / filling of joints with white cement etc: complete in all respect. (Imported Premium Quality costing Rs 1600 per square meter or above). as per sample approved by Engineer etc complete.  Wash Rooms Wall Dado	2,000	P.Sft	
61	Providing and fixing Roof Shade made of Fiber Glass Sheet 3 mm rest over frame structure of tubular pipe frame consisting of various pipes having sizes 38mm x 18mm, 18mm x 18mm and 25mm x 25mm (16guage) fixed with G.I pipe posts of 60 mm dia painted G.I pipes 10 ' high above ground and 2' buried under ground. This rate i/c all type of work such as cutting and fixing Fiber Sheet with tubular pipe frame fixing with nuts, bolts, bitumen washers etc complete in all respects i/c painting one coat of red oxide and two coats of enamel paint over metal iron work as per matching shade etc complete in all respects as per directives of Engineer Incharge	1,700	P.Sft	
62	Providing and fixing Cement Checquer Tiles Flooring (12"x12"x1" or above ) jointed in white cement and laid over bed of 1/2"thick grey cement send mortar ratio 1:3 i/c washing / filling of joints with white cement etc: complete in all respect (Premium Quality costing Rs 600 per square meter or above )	1,200	P.Sft	
63	Providing Making and Fixing MS Door net grill with 3/8" x 3/8" square rod and welded with MS Sheet 18 gauge and counter from 1-1/4" x 1-1/4" gauge.	450	P.Sft	
64	P/F Decorative False Ceiling of first quality MDF Lassani boards of various thicknesses ( 3/4", 1/2" & 3/8") with wooden logs as per requirement of Architecture Drawings and specifications provided i/c decorative paint or French polish as required and also making excess for decorative false ceiling LED Lights etc complete in all respects as per directives of Engineer In charge.	850	P.Sft	
65	Supplying and fixing False Ceiling of gypsum sheet (2' x 2' or 4'-0"X 2'-0" imported) in panels including making frame work of imported Aluminum 'T' Channels	14,300	P.Sft	

65.1	Providing & fixing reflected ceiling consisting of Aluminum framing as per given sizes, in gypsum board 1/2" thick, including bulk head / valance and open light box etc, fixed with regid adjustable hanging suspension system of GS (to make rust proof) including applying Matt Enamel paint roller applied (ICI or approved equivalent). Also making provision for dropped and punched including required height and light fixture Pelmet as shown in drawing. Complete as per detail / drawing and as directed by the Consultants.	7,200	P.Sft	
66	Providing and Fixing MS corrugated sheet of 20 SWG shade with 1-1/2"x1" MS tube 16 gauge and angle 1-1/2"x1-1/2"x 2/8 thick structure fixing with screw & welding pin for supporting.	2,500	P.Sft	
67	Providing and fixing JUNG-SHAHI Stone Tile on Face Elevation (Plain Stone Tile Duly Mixed With Ornamental Embarked Stone Tile as per Design Requirements) (8"x8" or 12" x6" x 3/4") jointed in white cement and laid over bed of 3/4"thick grey cement send mortar ratio 1:3 i/c washing / filling of joints with white cement etc: complete in all respect.	5,150	P.Sft	
68	Providing and fixing Stone Coping (12"x 2") with lining of 2" Thick jointed in white cement and laid over bed of 1/2"thick grey cement send mortar ratio 1:3 i/c washing / filling of joints with white cement etc: complete in all respect.	350	P.Rft	
69	ACP Cladding Sheet, BRANDED, "I-Bond", Premium American Brand,FR "PVDF Coated", Overall "4 mm" Thickness with "0.5 mm" Aluminum Skin on Front Side & 0.3 mm on Back Side & Polyethylene b/w Skins. KYNAR 500. PSB Test Passed. ISO & AusS Certified. 20 Years Shining Warranty. With Scaffolding & Electricity. Complete in all Respect with Fixing & Hardware Accessories.	4,500	P.Sft	
70	Providing and fixing Printed Glazed Ceramic Hala Pattern Tiles (Size 8" x 8") on wall facing or in dado jointed in white cement and laid over bed of 1/2"thick grey cement send mortar ratio 1:3 i/c washing / filling of joints with white cement etc: complete in all respect. (Premium Quality costing Rs 1000 per square meter or above)	200	P.Sft	

71	Providing & fixing wall cladding with M D F 1/2" thick board on both sides with back support with 3" x 1-1/2" Portal wooden frame with solignum treated, including 1/8 " thick oak ply cladding with making groove thick as per design drawing, approved polish finish three side (polish make by I.C.I approved or equivalent) etc complete in all respects as per directives of Engineer In charge.	4,500	P.Sft	
72	P/F wooden cabinet 16" deep (American / Italian Style) made up of frame of partal wood 2"x2" & shutter of chip board 3/4" with Formica on outer side i/c making drawn shelves etc: as per required colors catcher handle etc: as per required the cost also i/c T&P carriage from shop to site of work and fixing on wall with wooden Patti / breaker as directed by the Engineer Incharge.	1,350	P.Sft	
73	P/s wooden office table 2'-6"x 5'-0" beach wood with Oak finish i/c top glass of 6mm as per approved make and design given by Engineer In charge	50	Each	
73	P/S office chair Charister made or Equivalent as per design approved by engineer.  Low back  High back	180	Each	
74	Provide & install in line and level wooden floor (heavy commercial) / of approved make i/c rubber underlay, wood edge detail as per drawing, etc complete in all respect or as approved by the Consultants or Engineer. Basic price shall be Rs. 220.00 per Sq.ft.	80 1,050	Each P.Sft	
75	Providing and installation floor of machine made nylon carpet tile of approved make with color and design. Complete in all respects as approved by the Consultants or Engineer. Basic price shall be Rs. 240.00 per Sq.ft	2,000	P.Sft	
76	Provide and install in position 2mm to 3mm thick imported vinyl flooring in tile form of 12"x12" of approved quality and make, with good quality adhesive, complete in all respects or as approved by the Consultants / Engineer.	500	P.Sft	

77	Providing, making and fixing Rafter 2" thick having 1/2" thick MDF all side with required wooden frame or solid oak wood with solignum 1/8' thick oak wood ply rafters with approved polish finish fixed with nuts and bolts on walls and adjacent gypsum ceiling including applying lacquer polish finish, using approved quality hardware, glue, nails etc. complete as per approved by the Consultants / Engineer.  Rafters Size: 3" x 3" Solid Oak wood Rafters Size: 3" x 3" MDF with Oak ply	324 200	Rft Rft	
78	Providing & applying handmade heavy textured paint of ICI or Burger or approved equivalent of approved shade from ICI or burger color bank on external surface, i.e. walls, columns, beams etc. including preparation of base etc. complete at any height as per approved by Engineer.	1,200	P.Sft	
79	Provide and install in position Roll-up window blinds of approved colour, and specifications, of Imported chain operated Roller blind with approved sample including wastage, lifting, etc, complete as respect and as approved by Engineer.	900	P.Sft	
80	Providing, making and supplying Stainless Steel planter 16" dia and 20" high complete in all respect	10	each	
81	Making and fixing mild steel plate form 6"x3"x1/4" C channel with checker plate 4mm thick as per approved design including paint red oxide primary coat and 2 coat oil paint approved shade make with all respect etc complete. For Overhead fiber glass tank size 16'-0" x 6'-0'	1	each	
82	Making and fixing mild steel plate form C 4" x 2" x 1/4"channel with checker plate 4mm thick as per approved design including paint red oxide primary coat and 2 coat oil paint approved shade make with all respect etc complete. Size 22'-0" x 1'-0"	1	each	
83	Making of staircase with C channel 4" x 2" x 1/4" for plate form with checker plate 4mm thick step theard 9-1/2" wide 4'-0" welding fixing including premier coat of red oxide and 2 coat of oil paint approved shade make with all respect accessories etc complete (ground + 2 floor) Girls Hostel	1	each	

	PART 'A' CIVILWORK TOTAL				
86	Making and fixing galvanized iron SWG 18 duct for pipe covering on wall as per instruction of engineer size 2'-6" x 1'-0" x10'-6"	2		Each	
85	Making of main hole cover 2" x 1/8" for frame for base 1-1/2" x 1" with solid bar 3/8" dia with cement concrete etc complete	18		Each	
84	Providing and fixing stair case railing with mild steel pipe bluster 1-1/2" dia with 4 layer 5/8" dia and top railing 2" dia as per approved design with all respect etc complete.	150		Rft	

	PART 'B' INTERNAL WATER SUPPLY & SANITARY FITTINGS				
1	Providing & fixing English Commode with Seat cover including flushing cistern,tee stop cock etc complete in all respects (Porta / Marachi or Equivalent) (Classic Model)	20		Each	
2	Providing & fixing Orisa W.C 23" Clear including flushing cistern ,tee stop cock etc complete in all respects (Porta/ Marachi or Equivalent) (Classic Model)	20		Each	
3	Providing & Fixing Wash Basin size 24" x18" with wash basin mixture and pedestal etc complete in all respects (Porta/Marachi or Equivalent) (Classic Model)	35		Each	
4	Providing & Fixing Wash Basin size 24" x18" (Vanity type with top counter and wooden box) with wash basin mixture and pedestal etc complete in all respects (Porta/Marachi or Equivalent) (Classic Model)	17		Each	
5	Providing & fixing Urinal including flushing cistern, tee stop cock etc complete in all respects (Porta / Marachi or Equivalent) (Classic Model)	15		Each	
6	Supplying/Fixing White glazed Laboratory sink bowl of approved made and design (Standard Size) as per standard requirement i/c bolt kit brackets, c.p waste and waste pipe etc complete in all respects	18		Each	
7	Providing and fixing C.P Brass Double bib cock with Muslim Shower 1/2" dia (Master/Sonex or equivalent)	10		Each	

	1=		
8	Providing and fixing C.P Brass Fancy bib cock with crystal head 1/2" dia (Master / Sonex or equivalent).	48	Each
9	Providing and fixing C.P Brass Concealed Tee stop cock with crystal head 1/2" dia (Master / Sonex or equivalent)	24	Each
10	Providing and fixing C.P Brass Concealed stop cock with crystal head 1/2" dia (Master / Sonex or equivalent)	12	Each
11	Supplying/Fixing C.P Brass Surgical Elbow action Wash Basin Mixture of superior quality with C.P Head and long arm 1/2" dia etc complete in all respects	6	Each
12	Providing and fixing Stainless Steel Sink Size 40" x 20" ( with double Trey ) i/c C.P Brass Sink Mixture , C.P waste, P.V.C Waste Pipe, Bolt kit etc complete in all respects. (Superior quality and heavy gauge)	2	Each
13	Providing and fixing U.P.V.C. Floor Trap 6"x2" or 6"x3" dia i/c Steel floor Jali grade-I (AGM or equivalent) including cutting, fitting with collars, clamps and rubber solvent. This rate also includes making holes in walls, plinth, floor and roof for fixing pipe and making good in c.c. 1:2:4. Testing pressure head 200 feet.  Only Steel Jali 6" x 6" with waste pipe hole	24 36	Each Each
14	Providing and fixing U.P.V.C. Pipe grade-I (AGM or equivalent) including all fittings such bends tees etc with cutting pipe up to required length, fitting with collars, clamps and rubber solvent. This rate also includes making holes in walls, plinth, floor and roof for fixing pipe and making good in c.c. 1:2:4. Testing pressure head 200 feet.  4" Dia for Single Attached Lavatory  3" Dia for Single Attached Lavatory	200 200	P.Rft P.Rft
15	Providing and fixing U.P.V.C. pipe grade-I (A.G.M.or equivalent) including cutting, fitting with collars, clamps and rubber solvent. This rate also includes making holes in walls, plinth, floor and roof for fixing pipe and making good in c.c. 1:2:4. Testing pressure head 200 feet.		
	4" Dia for General Lavatory and out side 3" Dia for General Lavatory and out side	230 230	P.Rft P.Rft

16	Providing and fixing U.P.V.C. Branch with			
	Access door, grade-I (A.G.M or equivalent)			
	including cutting, fitting with collars, clamps			
	and rubber solvent. This rate also includes			
	making holes in walls, plinth, floor and roof			
	for fixing pipe and making good in C.C.1:2:4.			
	Testing pressure head 200 feet.	_	Fook	
	Plug Tee 4" X 4" Dia	5	Each	
	Plug Tee 3" X 3" Dia	5	Each	
17	Providing and fixing U.P.V.C. Plain. Tee			
''	4"x4" dia or 'Y' Tee grade-I (A.G.M. or			
	equivalent) including cutting, fitting with			
	collars, clamps and rubber solvent. This rate			
	also includes making holes in walls, plinth,			
	floor and roof for fixing pipe and making good			
	in c.c. 1:2:4. Testing pressure head 200 feet.  Plain or Y Tee 4" X 4" Dia	6	Each	
	Plain or Y Tee 3" X 3" Dia	6	Each	
	I Idiii Oi I 1663 A3 Dia	U	Lacii	
18	Providing and fixing U.P.V.C. Plug Bend			
	4"x4" dia with Access door, grade-I (A.G.M or			
	equivalent) including cutting, fitting with			
	collars, clamps and rubber solvent. This rate			
	also includes making holes in walls, plinth, floor and roof for fixing pipe and making good			
	in c.c. 1:2:4. Testing pressure head 200 feet.			
	<u>.</u>			
	Plug Bend 4" X 4" Dia	6	Each	
	Plug Bend 3" X 3" Dia	6	Each	
10	Draviding and fiving LLD.V.C. Plain Band 4"			
19	Providing and fixing U.P.V.C. Plain Bend 4" dia grade-I (A.G.M. or equivalent) including			
	cutting, fitting with collars, clamps and rubber			
	solvent. This rate also includes making holes			
	in walls, plinth, floor and roof for fixing pipe			
	and making good in c.c. 1:2:4. Testing			
	pressure head 200 feet.	40	FL	
	Plain Bend 4" Dia	12	Each	
	Plain Bend 3" Dia	8	Each	
20	Providing & fixing of PPR/pvc/cpvc AGM			
20	euilant PN-20 cold / Hot water pipes with all			
	required molded fittings PN-20, jointing pipe			
	with heat method, testing. This rate also i/c			
	cutting holes in wall plinth and roof for			
	consealed pipe fittings and making good in c.c 1:2:4 etc complete in all respects as per			
	specifications and instructions provided by			
	the Engineer In charge.			
(i)	40 mm	2,150	P.Rft	
(ii)	30 mm	1,130	P.Rft	
(iii)	25 mm	1,130	P.Rft	
(iv)	20 mm	300	P.Rft	
(v)	13 mm	410	P.Rft	

	T		I	<u> </u>	
21	Providing & fixing of PPR PN-20 Gate Valve with brass threads, jointing with already laid pipe by heat method, testing, etc complete in all respects as per specifications and instructions provided by the Engineer In charge.				
(i)	40 mm	2		Each	
(ii)	30 mm	4		Each	
(iii)	25 mm	4		Each	
(iv)	20 mm	6		Each	
(v)	13 mm	4		Each	
(*)	13 11111	7		Lacii	
22	Providing G.I pipes of approved standard company with fittings such as tee, bend, socket, elbow union & clamps where as required etc i/c threading, fixing cutting & fitting complete with & i/c the cost of breaking through walls & roof for making consealed, making good etc, painting two coats after cleaning the pipe etc, with white zink paint with pigment to match the colour of the building and testing with water to a pressure head of 200 feet and handling. (I.I.L.M or Equivalent).				
(i)	1/2" Dia pipe	829		P.Rft	
(ii)	3/4" Dia pipe	4,140		P.Rft	
(iii)	1" Dia pipe	650		P.Rft	
23	Providing and fixing C.P. Brass handle valve. (Made in Italy).				
(i)	1/2" Dia pipe	45		Each	
(ii)	3/4" Dia pipe	31		Each	
(iii)	1" Dia pipe	10		Each	
(,					
23	Providing G.I pipes of approved standard company with fittings such as tee, bend, socket, elbow. union & clamps where as required etc i/c threading, fixing cutting & fitting complete with & i/c the cost of earth excavation up to required depth and laying pipe in to the trench and refilling the trench i/c painting two coats of bitumen with hessian cloth after cleaning the pipe etc complete and testing with water to a pressure head of 200 feet and handling. (External I.I.L M or Equivalent).				
(i)	1-1/4" Dia pipe	80		P.Rft	
(ii)	1-1/2" Dia pipe	80		P.Rft	
(iii)	2" Dia pipe	100		P.Rft	

24	Providing and fixing Gun Metal wheel Threaded Valve (Made in Italy).			
(i) (ii) (iii) (iv)	1-1/4" Dia pipe 1-1/2" Dia Valve 2" Dia Valve 4" Dia Valve	4 4 2 2	Each Each Each Each	
25	Providing chambers 9" x 6" (inside dimensions) x 24" deep for stop cocks and valves etc. with 6" thick C.C 1:3:6 cast in situ walls, 6" thick C.C 1:4:8 in foundation 1/2" thick cement plaster 1:3 to all inside wall surface and to top 1" thick C.C 1:2:4 flooring complete with hinged cast iron cover and frame 9"x6" (inside) clear opening (wt 1/2" Qr) etc. fixed in cement concrete 1:2:4 including curing excavation back filling & disposal of earth etc. complete.	6	Each	
26	Supplying & fixing Bath room accessories set (9 Pieces) I/c towel rod, brush holder, Coat Holder & soap tray shelf of approved design i/c cost of screws, nuts etc Complete.(Master Brand or Equivalent).	6	Each	
27	Providing & fixing chrome plated brass towel rail complete with brackets fixing on wooden cleats with 1" long c.p brass screws. (Superior Quality).			
(i) (ii)	Towel Rail 36" long Towel Rail 30" long	6 6	Each Each	
28	Supplying & fixing soap tray of made plastic of Superior quality and design with fine finishing with c.p screws etc. complete.	12	Each	
29	Supplying & fixing C.P Brass Wash Basin Swan Type Piller Cock with crystal head 1/2" dia (Master / Sonex or equivalent).	12	Each	0
30	Supplying & fixing Electronic Hand Dryer of approved Make & Design (Imported).	6	Each	0
31	Providing & fixing Bavelled edge mirror of Belgium glass (Above 3.00 Sft) complete with 3" thick pre polished wooden border, 1/8" thick hard board and C.P. screws fixed to wooden pleat. (Superior Quality)	40	D 0"	
	•	40	P.Sft	0

(i) (ii)	Providing and laying of U-PVC Pipe of class 'B' suitable for external drainage work buried in ground under roads crossing as per specification with excavating trench for laying of pipe, bricks, warning tape, and back filling with new and fresh sand (4" below pipe and sides with leveling stacks), compaction and plugging of pipe ends etc complete in all respect as shown on drawing provided and as per directives of Engineer In charge.  12" Dia pipe  8" Dia pipe	550 850	P.Rft P.Rft	0
(iii)	6" Dia pipe	280	P.Rft	0
(iv)	4" Dia pipe	380	P.Rft	0
33 (a)	Supplying & fixing fiber glass tank of approved quality and design and wall thickness as specified i/c cost of notes, bolts and fixing in platform of cement concrete 1: 3: 6 and making connections for in -let out-let & over flow pipes etc. complete.  250 Gallons Fiber Tank	2	Each	
(b)	400 Gallons Fiber Tank	2	Each	
(c)	500 Gallons Fiber Tank	4	Each	
34	Providing and fixing Mono Block water pumping set size 1"x1-1/4" (Golden or Equivalent) with <b>1 H.P Motor</b> of 2800 RPM having single phase 220 Volts connection including base plate and also making C.C. 1:3:6 platform of required size and fixing with nuts and bolts complete in all respect. This rate also i/c 2-3/.036 P.V.C insulated power wiring, 10 Amp Main Switch for motor etc complete in all respects.	2	Each	
35	Providing and fixing Mono Block water pumping set size 2"x1-1/2" (Golden or Equivalent) with <b>2 H.P Motor</b> of 2850 RPM having single phase 220 Volts connection including base plate and also making C.C. 1:3:6 platform of required size and fixing with nuts and bolts complete in all respect. This rate also i/c 2-3/.036 P.V.C insulated power wiring, 10 Amp Main Switch for motor etc complete in all respects.	2	Each	0

36	Providing and fixing Mono Block water pumping set size 2"x 2-1/2" (Golden or Equivalent) with 5 <b>H.P Motor</b> of 2850 RPM having Three phase 440 Volts connection including base plate and also making C.C. 1:3:6 platform of required size and fixing with nuts and bolts complete in all respect. This rate also i/c 2-3/.036 P.V.C insulated power wiring, 10 Amp Main Switch for motor etc complete in all respects.	2	Each	0
37	Providing and fixing water pumping set with Siemen motor and Javed pump <b>25 H.P. 2850 RPM</b> three phase 440 Volts with pump size 8"x 6" suction and delivery 200 ft. head including base plate and also making C.C. 1:3:6 platform of required size and fixing with nuts and bolts complete in all respect. This rate also i/c 3-7/.064 P.V.C insulated power wiring, auto-matic starter for motor etc complete in all respects.	1	Each	0
38	Construction manhole or inspection chamber for the required dia of circular sewer and 3'-0" (900 mm) depth with walls(6" thick) of C.C Plain ratio 1:3:6 cement plastered 1:3 1/2" thick inside of walls and I" (25mm) thick over benching and channel i/c fitting C.I manhole cover with frame of clear opening (1-/2' x 1., 1/2' (457x457 mm) of 1.75 Cwt. (88.9 kg) embedded in plain C.C 1:2:4 and fixing I" (25 mm) C/C duly painted etc. complete as per specification and drawings provided by Engineer Incharge.			
	(i) Circular Man Hole (24" Dia i/i with depth of 36")	18	Each	
	(ii) Circular Man Hole (36" Dia i/i with Depth of 48")	12	Each	
39	Providing and Fixing Brass Foot valve of 1" Dia.	4	Each	
40	Providing and Fixing Gate Valve AGM of Dia.	21	Each	
41	Providing and Fixing Brass check Valve of 2" Dia	2	Each	

42	Providing and laying of P Pipe of PN-10 category i/c fittings & specials suitable for external water supply work buried in ground under roads crossing as per specification with excavating trench for laying of pipe, bricks, warning tape, and back filling with new and fresh sand (4" below pipe and sides with levelling stacks), compaction and plugging of pipe ends etc complete in all respect as shown on drawing provided and as per directives of Engineer In charge.  6" Dia pipe	260		P.Rft	0
		200		1 .100	J
43	Supply / Fixing M.S flanges 3/8" thick of 4" Dia	8		Each	0
44	Providing and Fixing Brass check Valve of 4" Dia	2		Each	-
45	UPVC Foot Valve of 6" Dia	2		Each	-
46	S/F of G.I Barred Nipple of 4" Dia	6		Each	0
47	Supply / Fixing U-PVC flanges 3/8" thick of 4" Dia	2		Each	0
48	Providing and fixing UPVC Pipe Schedule 80 a) 1/2" dia b) 3/4" dia c) 1" dia d) 1-1/4" dia e) 1-1/2" f) 2" dia	200 350 220 140 140 160		Rft Rft Rft Rft Rft Rft	
				TOTAL	
	Part 'C' INTERNAL SUI	GAS FITT	INGS		
1	Providing and fixing Brass Gas Cock 1/4" dia imported	16		Each	
2	Providing & fixing of Gas Burner (Three Ways Table Top) of approved make and design with necessary fittings by approved method, testing etc complete in all respects as per specifications and instructions provided by the Engineer Incharge. (Imported heavy duty)	5		Each	
3	Providing & fixing of Lab Gas Burner of approved make and Design with necessary fittings by approved method, testing etc complete in all respects as per specifications and instructions provided by the Engineer Incharge	15		Each	

4	Providing & fixing of Gas Geyser of approved and Design (35 Liters) with imported pilot and necessary fittings by approved method, testing etc complete in all respects as per specifications and instructions provided by the Engineer Incharge	7		Each			
5	Providing & fixing of PE-80 (Polyethylene-Flex) sui gas pipes with all required Moulded fittings of PE-80, jointing pipe with approved method, testing, excavating trench in existing external soil, laying pipe, refilling the trench compaction etc complete in all respects as per specifications and instructions provided by the Engineer In charge.  20 mm	40		P.Rft			
(i) (ii)	13 mm	40 40		P.Rit P.Rft			
6	Providing & fixing of PE-80 (Polyethylene-Flex) Gate Valve with brass threads, jointing with already laid pipe by approved method, testing etc complete in all respects as per specifications and instructions provided by the Engineer In charge.						
(i)	20 mm	2		Each			
(ii)	13 mm	2		Each			
7	Removing & Re-fixing of Existing Geyser i/.c replacement of damaged copper rods and other fittings where as required.	10		Each			
8	Supply/Fixing Complete Pilot Kit i/c Thermo Stat (Imported)	10		Each			
9	Supply/Fixing Complete C.P Brass Safety Valve of 1" Dia (Imported)						
		10		Each			
	PART 'C' INTERNAL SUI GAS TOTAL						
PART 'D' INTERNAL ELECTRIFICATION WORK							
1	Wiring for light, fan or plug point with 1.5 sq.mm single core, PVC insulated wire copper conductor wire in PVC Patti or cap casing 0n wall or roof etc, including 1 sq.mm single core PVC insulated wire as ECC as required.						
(i)	(From D. B to Switch Board)	400		P. Point.			
(ii)	(From Switch Board to Point)	460		P. Point.			
(iii)	(From Point To Point )	110		P. Point.			

2	Wiring for call bell point with 1.5 sq.mm single core, PVC insulated wire copper conductor wire in PVC Channel Patti or cap casing 0n		
	wall or roof etc, including 1 sq.mm single core PVC insulated wire as ECC as required	5	P. Point.
3	Wiring for two way point with 1.5 sq.mm single core, PVC insulated wire copper conductor wire in PVC Channel Patti or cap casing on wall or roof etc, including 1 sq.mm single core PVC insulated wire as ECC as required.	5	P. Point.
4	Wiring for plug point with 1.5 sq.mm single core, PVC insulated wire copper conductor wire in PVC Channel Patti or cap casing over wall ,column, roof etc, including 1 sq.mm single core PVC insulated wire as ECC as required . (Nearest light plug).	30	P. Point.
5	Circuit Wiring for distributing circuits with 2-1/1.38(3/.036) PVC insulated wire in PVC Channel Patti or cap casing on wall or roof		
	(Maximum length of circuit from D.B To Switch Board should be 200 Rft or more).	55	Each
6	Circuit Wiring for power point with 2-7/0(7/.044) PVC insulated wire with 1-1/36 as ECC in PVC Channel Patti or cap casing on wall or roof. (Maximum length of power wiring from D.B to Point should be 160 Rft).	20	Fach
7	Providing & fixing 10 Amps polycarbonate flame retardant one way switch with fancy gang plate fixed on die fabricated powder coated metal board recessed in wall or column including connection as required (E31/2/3A Clipsal Make)	30	Each
(a)	One gang Switch Plate	21	Each
(b)	Two gang Switch Plate	42	Each
(c)	Four gang Switch Plate	50	Each
(d)	Six gang Switch Plate	55	Each
(e)	Eight gang Switch Plate	90	Each
8	Providing & fixing 10Amps polycarbonate flame retardant bell push with fancy gang plate fixed on die fabricated powder coated metal board recessed in wall or column including connection as required (E31/MBPR Clipsal Make).	6	Each
	Olipsai Mare).		Lacii
9	Providing & fixing 10Amps polycarbonate flame retardant two way switch with fancy gang plate fixed on die fabricated powder coated metal board recessed in wall or column including connection as required.		
	(E31/2/3A Clipsal Make).	6	Each
	· · · · · · · · · · · · · · · · · · ·		

10	Providing & fixing 10Amps polycarbonate flame retardant 2-pin switch socket unit (Universal) with fancy gang plate fixed on die fabricated powder coated metal board recessed in wall or column including connection as required. (E-15U Clipsal Make)	50	Each	
11	Providing & fixing 13Amps polycarbonate flame retardant 3-pin switch socket unit (Universal) with fancy gang plate fixed on die fabricated powder coated metal board recessed in wall or column including connection as required (Clipsal Make) with back & boxing.	130	Each	
12	Providing & fixing 15Amps polycarbonate flame retardant 3-pin switch socket unit (Universal) with fancy gang plate fixed on die fabricated powder coated metal board recessed in wall or column including connection as required (Clipsal Make) with back & boxing.	130	Each	
13	Providing & fixing A.C/D.C Door Bell (superior quality imported)on die fabricated powder coated metal board recessed in wall or column including connection as required.	6	Each	
14	Providing & fixing 3"x4"x5" size (14SWG) thick recessed type fan clamp box 5/8" dia MS bar fan clamp fixed in roof at casting time as required.	48	Each	
15	Making hole in the wall for metallic exhaust fan and fixing of hold fast, dully plaster and making good the damage surface as required.			
(i) (ii) (iii) (iv)	8" Dia Sweep 10" or 12" Dia Sweep 18" Dia Sweep 24" Dia Sweep	10 10 10 10	Each Each Each Each	
16	Providing and fixing 6 Amps plastic ceiling rose on PVC round block /round cover fitted on surface including connection as required.	48	Each	
17	Providing and installing 25 CM (12") sweep plastic body Exhaust fan complete with blades, motors, etc fixed in existing hole including connection with 14/.0076" flexible wire complete as required (without regulator) Millat/Pak/Asia/Younus/Climax/Royal.	2	Each	
	willian an Asia i bullus/billian/Noyal.		Lacii	

		T	T	
18	Providing and installing 60CM (24") Wall Bracket Fancy Fan including connection with 14.0076" flexible wire complete as required (Millat / Pak / Asia / Younus / Climax / Royal).	10	Each	
19	Providing and installing 140 CM (56") sweep ceiling fan with blades, canopy, standard length of down rod including connection with 14.0076" flexible wire complete as required (without regulator) Millat/Pak/Asia/Younus/Climax/Royal.	38	Each	
20	Providing & fixing 15 Amps poly carbonate flame retardant 400 watts fan dimmer with plate fixed on die fabricated powder coated metal board recessed in wall or column including connection as required (E32V400F Clipsal Make)	48	Each	
21	Providing & Laying of following sizes of 3-1/2 core PVC insulated & PVC sheathed 600/1000 volt grade with standard copper conductor unmoored L.T cable in existing all kind of conduit or cable duct as per Approved specification as required.	225	P.Rft	
22	Providing and fixing Earth set with 2' x 2' x 1/4" copper plate buried in the ground at a depth of 12 feet or less if water comes out from the ground level (with salt and charcoal, or Earth chemical powder) etc Making the pit 12 feet deep by excavation of all type of soil (except soft or hard rock) i/c fixing of 8 SWG copper wire in 1/2" G.I conduit complete in all respects as required.	1	P.Job	
23	Providing & Fixing basic batten, surface type, fitting complete with TLD 1x36W white day light lamp starter, electronic ballast as Philips Cat. (TMS015/136 L.E.D)	10	Each	
24	Providing & Fixing basic batten, surface type, fitting complete with TLD 2x36W white day light lamp starter, electronic ballast as Philips Cat. (TMS015/136 L.E.D)	14	Each	
25	P/Fixing 2'-0" x 2'-0" Fancy False Celling Circo Fan(imported) of approved make and design etc complete in all respects as per directives of Engineer Incharge.	12	Each	
26	Providing & Fixing basic batten, surface type, fitting complete with TLD 4x36W (2'-0" LONG), ALUMINIUM CASING (L.E.D), white day light lamp starter, electronic ballast as Philips Cat. (TMS015/136)	12	Each	

				1
27	Providing and fixing L.E.D Energy Saver 12 Watts Phillips i/c wall type or ceiling fancy bracket	12	Each	
28	Providing and fixing L.E.D Energy Saver 20 Watts Phillips i/c wall type or ceiling fancy bracket	12	Each	
29	P/Fixing LED Pendent Light with 18 watts bulb in a fancy glass globe casing hanging on 4' Long hallow pipe rod of 3/4" dia pipe of approved make and design etc complete in all respects as per directives of Engineer Incharge.	12	Each	
30	P/Fixing LED Fancy Light with 18 watts bulb and 12"x12" fancy bracket of approved make and design etc complete in all respects as per directives of Engineer Incharge.	12	Each	
31.1	P/Fixing LED Fancy Light with 42 watts 2'x2' fancy of approved make and design etc complete in all respects as per directives of Engineer Incharge.	50	Each	
i ii iii	Supply & Installation of following Main / Distribution Panel Boards of approved make and design concealed in wall/surface mounted or floor standing. 1.5/2/3 mm sheet steel fabricated powder coated , suitable for 500 volts, 3 phase ,4 wires,50 Hz, incorporate following components & configuration, complete with all mounting & connecting accessories as per Electrical Drawings attached etc complete in all respect as per specification provided and instructions given by the Engineer Incharge.  SMDB-MB EDB-EME EDB-MB-1	2 4 4	Each Each Each	
32 a	Supply, Laying, termination and commissioning of following copper conductor cable in already laid PVC conduit / cable tray / trench as required, as per drawings, specification and instructions given by Engineer Incharge (Cu /pvc/ pvc cable , 600/1000v, Pak /Pioneer/AEG Cables).  4 Core - CU/PVC/ PVC Cable (600/1000V)			
		650	P.Rft	
i ii	4 Core - 6 Sq.mm 4 Core - 10 Sq.mm	650 450	P.Rft	
l "	4 Core - 16 Sq.mm	500	P.Rft	
iv	4 Core - 25 Sq.mm	300	P.Rft	
V	4 Core - 35 Sq.mm	650	P.Rft	
vi	4 Core - 70 Sq.mm	150	P.Rft	
vii	4 Core - 95 Sq.mm	150	P.Rft	

			T T
С	1 Core - PVC Cable as ECC (600/1000V)		
i	1 core -10 Sq.mm	1,000	P.Mtr
33	Providing and fixing L.E.D Energy Saver of approved make Design.		
i.	12 Watts	40	Each
ii.	24 Watts	110	Each
iii.	45 Watts	20	Each
iv.	85 Watts	23	Each
v.	400 Watts	9	Each
34	Providing & Fixing G.I Fan rod 3/4" Dia & 4' long duly painted with enamel paint of matching shade	80	Each
35	P/F Circuit breaker 6 Amp to 32 Amp. Single pole i/c. fixing on prepared board and necessary connection.	30	Each
36	P/F Circuit breaker 32 Amp. Double Pole i/c fixings on prepared board and necessary connection.	12	Each
37	P/F Circuit breaker 32 Amp T.Pole i/c. fixing on prepared board and necessary connection.	24	Each
38	P/F Safety Breaker 20 Amp i/c necessary fixings on prepared board and necessary connection.	24	Each
39	Providing and Fixing Stabilizer of approved make & design.		
(i)	Universal A-70 (7000 Watts)	8	Each
(ii)	Universal A-50 (5000 Watts)	4	Each
(iii)	Universal A-30 (3000 Watts)	4	Each
(iv)	Universal A-10 ( 1000 Watts ) for P.C	4	Each
40	Providing and prepare Earth Pit with 3 meter long, 20 mm dia copper rod type electrode for earthing system at the end of every circuit directly driven to ground to obtain earth resistance not more than 3 ohm including 2 x 16 sq. mm single core PVC insulated wire or 2 x 16sq mm bare copper conductor in 50 mm dia G.I pipe, from earth rod to lighting pole. Inspection pit 380 x 380 x 460mm deep (min) with heavy duty C.I cover, appropriate size of Upvc conduit for leads, complete as per detail drawing & instruction of consultant. providing as built drawings, test reports documents to Employer / Consultant representative. Complete in all respects.	2	Each

41	Providing and Installation of 200 mm x 100 mm wide Fiber cable tray including cover.	200	P.Rft			
42	Supply, Installation, Testing & Commissioning of following Air Conditioning Split Unit Complete (Invertor Type) in all respect ready to operate complete in all respect. The work should be completed with control wiring with limited copper conducting as required.  (Acson / Mitsubishi / Gree).					
a)	1.0 Ton Wall Mounted Split Type.	10	Each			
b)	1.5 Ton Wall Mounted Split Type.	15	Each			
c)	2.0 Ton Wall Mounted Split Type.	25	Each			
d)	2.5 TR wall mounted type A/c	2	Each			
,	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	_				
43	Supply / Installation and Commissioning of Refrigerant copper piping (Liquid + Gas-1/2 + 1/4 +5/8+3/8) make Muller USA with expanded rubber foam Insulation (Make Aeroflex) Gas Charging if required. Control wiring in PVC conduit between internal and external units etc complete in all respects.	450	P.Rft			
44	Providing, laying, testing and commissioning of following size telephone & Data Cable in already laid PVC pressure pipe conduit or PVC channel or cable tray/trench as shown on drawing and as per instruction of consultant complete in all respect.  CAT -6 (Data Cable and Telephone)	1,350	P.Rft			
45	Providing/Supplying & Fixing net solo pot switch (Sisco) 3 M 24 patches penal (loaded) with 9-U network rack, patch code 1 & 2 meter long, 3 m Cad I.O complete.	1	Each			
		•	20011			
46	Supply/ Fixing of Industrial UPS 5 Kva i/c wiring with Dry Battery and necessary angle iron bracket for erecting UPS (Imported).	2	Each			
47	Providing & Fixing PVC Insulated RJ-6 copper coaxial wires for TV cable i/c hooks and clips where as required.	120	P.Rft			
	PART 'D' INTERN	IAL ELECT	RIFICATION WORK			
	TELEPHONE & DATA SYSTEM					
7.1	Supply & installation of following 0.6mm dia.					
	shielded telephone cables in 25 mm dia PVC conduit.					
a)	Cat - 6	750	Mtr			
b)	Telephone cable 50 pair.	105	Mtr			
		125				

7.2	Supply & installation of following boards as per drawings fabricated from 16SWG sheet steel powder coated box with hinged covered door.			
a)	Telephone Junction Box with. (8 x 25 pair punch block) tag block.	1	No.	
7.3	Supply & installation of following telephone outlets (i/o + Face Plate) with back box.(Hussain make)			
a)	RJ-45 for telephone system.	30	No.	
b)	RJ-45 for Data system.	30	No.	
c)	RJ-45 for Data system. (Duplex)	5	No.	
	The To Tot Data System (Dapter)	3	INO.	
7.4	Supply and installation of Cat-6 giga speed cable AT & T / clipsal make for data system in 25 mm dia PVC conduit.	800	Mtr	
7.5	Card Access Control System	1	No.	
7.6	Wiring for Card Access	1	No.	
7.7	UPS 10 KW	1	No.	
7.8 a)	Following CAT-6, Patch Panels equipped with RJ-45 I/Os for Data communication system with rear cable organizer including all labeling and all mounting accessories. Complete in all respects.  24-port CAT-6 patch panel for data	2	No.	
7.9 a)	Following CAT-6, Patch Panels equipped with RJ-45 I/Os for Voice communication system with rear cable organizer including all labeling and all mounting accessories. Complete in all respects.  24-port CAT-6 patch panel for Voice	2	No.	
	, p.s.e pse	_	140.	
7.10	Front Cable Organizer for Voice & Data patch panels / wiring blocks with complete labeling and dressing for incoming cable management.	4	No.	
7.11	Following CAT-6, factory certified patch cords of specified color having RJ-45 connectors at both ends for voice communication.			
		00	NI-	
a)	3 meter long.	20	No.	
b)	1 meter long.	20	No.	

7.12	Following CAT-6, factory certified patch cords of specified color having RJ-45 connectors at both ends for Data communication.				
a)	3 meter long.	20	No.		
b)	1 meter long.	20	No.		
7.17	Supply, Installation, Testing and Commissioning of Data Switch (10G) for Cat-6 Cable.	1	No.		
7.18	Supply and Installation of 42U Floor Mounted Communication Rack. Suitable for installation of servers, switches and related equipment etc. Complete with vertical cable managers. Rack shall be equipped with power distribution units (PDUs) with at least 5 imported power sockets etc. Complete in all respects.	1	No.		
7.19	<b>Testing and Commissioning</b> of all above items termination and connectivity at both ends, including submission of detailed test report from the Principals.	1	job		
	TOTAL				

Sr.#	Description	Unit	Qty	Rate	Amount (Rs.)
	AIR CONDITIO	NER WO	RK		
	GROUND FLOOR TO SIX FLOOR				
1	Supplying, testing & commissioning High ambient split type air conditions wall mounted with decorative grill electric-220 volt-50HZ,single phase capacity -12000 Btu (1 Ton net capacity) out Door condenser tube 360 psi tested evaporator 180 psi tested operation condition ambient 55 celicuse compressor T3 type tested on 60 celicuse ambient. i/c making holes with diamond bit, nut, bolts including cartage etc complete in all respect, as per sample approved by Engineer.	Nos.	20		
2	Supplying, testing & commissioning High ambient split type air conditions wall mounted with decorative grill electric-220 volt-50HZ, single phase capacity -18000 Btu (1.5 Ton net capacity) out Door condenser tube 360 psi tested evaporator 180 psi tested operation condition ambient 55 celicuse compressor T3 type tested on 60 celicuse ambient. i/c making holes with diamond bit, nut, bolts including cartage etc complete in all respect, as per sample approved by Engineer.	Nos.	45		
3	Supply & installation of split type air condition copper pipe including aeroflex & control wiring etc complete.	Rft	2,150		
4	Supply & installation angle iron stand as a foundation of split outer unit including fixing coloring etc complete.	Nos.	118		
5	Supply & installation of following sizes of G.I (14 gauge) Powder coated cable tray. Size 6" x 3"	Rft	800		
6	Supply & installation of best quality drain pipe UPVC including accessories such as bend, tees, etc complete.  3/4" Dia	Rft	80.00		
				TOTAL	